

Robust and durable

DUAL AXIS ANGLE

The AusProTec™ Dual Axis Angle Sensor is a small and compact aluminium unit. Its rugged design and features provide a robust solution for mining or industrial applications. The platform angle is required to be between 0 and 90 degrees on both the X and Y axes. Therefore, the unit must be mounted on a flat surface. Once powered, the sensor will tilt on either axis.

Features

- Multi-voltage
- 1 x relay output (positive)
- Hysteresis 0.05 degrees
- Sealed to IP66
- Cable length 30 cm
- Dimensions 84 mm (D)

By clicking Accept All Cookies, you agree to the storing of cookies on your device to enhance site navigation, analyze site usage, and assist in our marketing efforts. [Cookie Notice Link](#)

Cookies Settings

Strictly Necessary Cookies
 Functional Cookies
 Targeting Cookies
 Social Media Cookies

Save Choices

Accept Only Necessary Cookies

Accept All Cookies

2/24 VDC
positive 0.2 amp max)
ction
ction
ction

Reference: SBAP0615125



RCT
 Head Office
 Unit 1-5/511 Abernethy Rd
 Kewdale WA 6105, Australia
 sales@rct-global.com

Australia +61 8 9353 6577
 Africa +27 83 292 4246
 Canada +1 705 590 4001
 Central Asia +7 910 411 1174
 USA +1 801 938 9214
 South America +56 22 4423 6600