

# Compact, efficient and technically superior

## MINI SWITCH MODE VOLTAGE CONVERTOR

The success of the “Maxi” Switch Mode Voltage Convertor range of heavy duty 24-12VDC voltage converters has led to RCT developing a new, compact version for low power applications.

The innovative “Mini” series range is targeted at the light vehicle market and is ideal for powering communications, instrumentation and other electronic equipment.

The new Switch Mode Voltage Convertor is enclosed in an extruded aluminium housing which is not only technically superior but practical and stylish.



Referencia: SBAP0513061



RCT  
Head Office  
Unit 1-5/511 Abernethy Rd  
Kewdale WA 6105, Australia  
sales@rct-global.com

Australia +61 8 9353 6577  
Africa +27 83 292 4246  
Canada +1 705 590 4001  
Central Asia +7 910 411 1174  
USA +1 801 938 9214  
South America +56 3 5229 9409

Copyright © 2023 Remote Control Technologies Pty Ltd. Images for illustration purposes only. Discover more @ rct-global.com

## Características

- Purpose designed - The new purpose built extruded housing with moulded end caps is as functional as it is attractive. The new design features effective heat dissipation, easy mounting, compact size and no sharp edges.
- Self diagnostics - Visual indication of the system status provides important information for both users and installers. The tri-colour LED will display an array of symptoms to assist in troubleshooting on-board problems.
- Corrosion resistant - Only high quality, marine grade components are used in construction. All hardware used in assembly is non-ferrous and the terminals are all plated brass. Circuit boards are tropicalized for ultimate protection.
- Heavy duty terminals - Connection is made safe and sure by using heavy-duty custom designed terminals. The connectors are protected by insulated barriers to prevent inadvertent shorting. All hardware is electrical grade and non-corrosive.
- Easy access cover - The unique extruded cover closes to protect the terminals and electronics from external objects including fingers. This prevents inadvertent short circuiting, ensuring safety and providing peace of mind.
- Diagnostics - This design provides valuable feedback to installers and operators. An LED displays the system status and will indicate standby power, low input voltage, over temperature, overload and output short circuit.
- Protection - Featuring a range of devices designed to protect the electronics from various connection and application problems. The units are protected against short circuit, overloading and excessive temperature. An internal fuse protects the electronics
- Performance - Designed to operate in high ambient temperatures under constant load with precise voltage regulation and superior noise filtering.

## Especificaciones

Model	7819	7823
Continuous Load Rating @ 30°C (80°F)	7 Amps @ 13.7VDC	10 Amps @ 13.7VDC
Peak Load Rating @ 30°C (80°F)*	10 Amps @ 13.7VDC	13 Amps @ 13.7VDC
Length Overall	120mm (4.725")	145mm (5.710")
Width Overall	80mm (3.150")	80mm (3.150")
Height Overall	40mm (1.575")	40mm (1.575")
Peso	270 grams (9.55 oz)	325 grams (11.45 oz)
Input Voltage Range	19 – 33VDC	-
Output Voltage	13.7VDC nominal (up to the maximum rated load)	
Standby Current Draw	Ø20mA	
Power Conversion Efficiency @ 30°C (80°F)	Typically 93%	
Output Ripple	Less than 20mV Peak to Peak	
Temperatura de Operación	-25°C to + 45°C	
Operating Humidity	Ideally less than 90%	
Enclosure Material	Marine grade aluminium dye anodised	
End Cap Material	Injection moulded electrical grade ABS/PC plastic	
Terminal Cover Material	Extruded temperature resistant ABS	
Transient Voltage Protection	Filtering - Purpose designed circuit	
Overload/Short Circuit Protection	Shutdown - Current sensing circuit (automatic reset)	
Input Under Voltage Protection	Shutdown - Voltage sensing circuit (automatic reset)	
Over Temperature Protection	Shutdown - Temperature sensing circuit (automatic reset)	
Output Over Voltage Protection	Internal Fuse – Zener crowbar circuit (not user serviceable)	
Input Reverse Polarity Protection	Internal Fuse – Diode bypass circuit (not user serviceable)	
Terminaciones	Power – 6-32 UNC H/D screw terminal. Auxiliary – Euro terminal block	
Conformity	EMC – Australian AS2064 and European EN50081-1 / EN50082-1	
Certification	EMC – Australian C Tick mark and European CE mark	

Referencia: SBAP0513061



RCT  
Head Office  
Unit 1-5/511 Abernethy Rd  
Kewdale WA 6105, Australia  
sales@rct-global.com

Australia +61 8 9353 6577  
Africa +27 83 292 4246  
Canada +1 705 590 4001  
Central Asia +7 910 411 1174  
USA +1 801 938 9214  
South America +56 3 5229 9409

Copyright © 2023 Remote Control Technologies Pty Ltd. Images for illustration purposes only. Discover more @ rct-global.com

Piezas

APN: 7819

VOLTAGE CONVERTOR 24-12VDC 7A

Referencia: SBAP0513061



RCT	Australia +61 8 9353 6577
Head Office	Africa +27 83 292 4246
	Canada +1 705 590 4001
Unit 1-5/511 Abernethy Rd	Central Asia +7 910 411 1174
Kewdale WA 6105, Australia	USA +1 801 938 9214
	South America +56 3 5229 9409
sales@rct-global.com	

Copyright © 2023 Remote Control Technologies Pty Ltd. Images for illustration purposes only. Discover more @ rct-global.com