

# Fire Controllers

## Australian Standard Fire Status Panel

The Muirhead® Fire Status Panel is designed and built to the latest Australian Standards AS5062.

The panel will monitor the status of the fire bottle from two pressure switch inputs.

The low pressure input warns the operator when the bottle pressure is below the desired KPA level.

The shutdown pressure switch will trigger when the bottle has been discharged. It also has a key switch for override and push button for extended shutdown when activated.



### Caractéristiques

- Multi Voltage
- Solid State Technology
- Programmable shutdown
- One Shot Extension
- Key Switch Override
- IP65 Panel

### Specifications

IP	IP65
Dimensions	120mm x 80mm x 55mm
Weight	0.5 kg

### Pièces

- ↪ APN: 0475 PRESSURE SWITCH 1200KPA FALLING 1/8NPT DUAL CIRCUIT
- ↪ APN: 2348 PRESSURE SWITCH 900KPA FALLING 1/8NPT DUAL CIRCUIT
- ↪ APN: 4800 PRESSURE SWITCH 200KPA FALLING 1/8NPT DUAL CIRCUIT
- ↪ APN: 5236 PRESSURE SWITCH 1050KPA FALLING 1/8NPT DUAL CIRCUIT
- ↪ APN: 5884 FIRE SHUTDOWN CONTROLLER MULTI VOLTAGE AS5062 SPECIFICATION

Reference: SBMH0615117



RCT  
Head Office  
Unit 1-5/511 Abernethy Rd  
Kewdale WA 6105, Australia  
sales@rct-global.com

Australia +61 8 9353 6577  
Africa +27 83 292 4246  
Canada +1 705 590 4001  
Central Asia +7 910 411 1174  
USA +1 801 938 9214  
South America +56 3 5229 9409

Copyright © 2023 Remote Control Technologies Pty Ltd. Images for illustration purposes only. Discover more @ rct-global.com