



Fire Controllers

Australian Standard Fire Status Panel

The Muirhead® Fire Status Panel is designed and built to the latest Australian Standards AS5062.

The panel will monitor the status of the fire bottle from two pressure switch inputs.

The low pressure input warns the operator when the bottle pressure is below the desired KPA level.

The shutdown pressure switch will trigger when the bottle has been discharged. It also has a key switch for override and push button for extended shutdown when activated.



Features

- Multi Voltage
- Solid State Technology
- Programmable shutdown
- One Shot Extension
- Key Swich Override
- IP65 Panel

Specifications

IP	IP65
Dimensions	120mm x 80mm x 55mm
Weight	0.5 kg

Parts

- ↪ APN: 0475 PRESSURE SWITCH 1200KPA FALLING 1/8NPT DUAL CIRCUIT
- ↪ APN: 2348 PRESSURE SWITCH 900KPA FALLING 1/8NPT DUAL CIRCUIT
- ↪ APN: 4800 PRESSURE SWITCH 200KPA FALLING 1/8NPT DUAL CIRCUIT
- ↪ APN: 5236 PRESSURE SWITCH 1050KPA FALLING 1/8NPT DUAL CIRCUIT
- ↪ APN: 5884 FIRE SHUTDOWN CONTROLLER MULTI VOLTAGE AS5062 SPECIFICATION

Reference: SBMH0615117