

No Cables, No Worries

1 Channel Wireless Transmitter and Receiver Kit

The Maxi Vision® Wireless 1 Channel Transmitter and Receiver Kit is robust in design and ideally suited to industrial and mining applications.

Housed in a diecast, IP69K waterproof enclosure, these units can withstand the harshest of environments.

With a range of up to 100 metres (328 feet), this kit has specifically been designed for vehicles where it is difficult to hard wire connect the camera directly to the monitor.

Upon request, multiple transmitter units can be paired to one receiver.



Features

- IP69K waterproof
- All diecast case
- Easily paired
- Multiple transmitters to one receiver (optional)
- Rear digitised wireless solution (frequency hopping)
- Minimised image delay
- Maximum 100 metre (328 feet) transmission distance







Specifications

| Frequency | 2400 - 2483.5Mhz |
|-----------------------|---|
| Frame Rate | 30fps |
| Transmission Range | Maximum 100m (328') (Open Field) |
| IP Rating | IP69K |
| Operating Temperature | -20°C to 70°C (-4°F to 158°F) |
| Power | 12 / 24 VDC |
| System Latency | 120ms |
| Dimensions | 87mm x 94mm x 25mm (3.42" x 3.7" x 0.98") (Each Unit - TX and RX) |
| Weight | 332g (0.73lbs) (Each Unit – TX and RX) |

Parts

APN: 15014

WIRELESS TRANSMITTER AND RECEIVER KIT 1 CHANNEL

Reference: SBAP0421002



RCT Head Office

Unit 1-5/511 Abernethy Rd Kewdale WA 6105, Australia

sales@rct-global.com

Australia +61 8 9353 6577 Africa +27 83 292 4246 Canada +1 705 590 4001 Central Asia +7 910 411 1174 USA +1 801 938 9214 South America +56 3 5229 9409

Copyright © 2023 Remote Control Technologies Pty Ltd. Images for illustration purposes only. Discover more @ rct-global.com