

Unique, compact & easy to install

102dB DUAL TONE WARNING ALARM

The AusProTec™ Dual Tone Warning Alarm provides a unique, audible alarm for alerting or reversing situations.

It is temperature rated to -40°F to 185°F (-40°C to 85°C) and sealed in epoxy resin for protection against dust, moisture and vibration.

This alarm is IP64 rated and CE, UL and R10 certified.



Features

- IP64 rated
- CE, UL and R10 Certified
- 2-wire installation
- Epoxy resin sealed
- Dual tone / fast pulse output

Specifications

IP Rating	IP64
Certification	Ce, ul, r10
Temperature Rating	-40°F to 185°F (-40°C to 85°C)
Voltage	12 / 24VDC
Amperage	0.9A
dB	102

Parts

APN: 16635

WARNING ALARM 102dB 12 / 24VDC 2 WIRE DUAL TONE REPLACES FS255 (6162)

Reference: SBAP0821001



RCT
Head Office
Unit 1-5/511 Abernethy Rd
Kewdale WA 6105, Australia
sales@rct-global.com

Australia +61 8 9353 6577
Africa +27 83 292 4246
Canada +1 705 590 4001
Central Asia +7 910 411 1174
USA +1 801 938 9214
South America +56 3 5229 9409

Copyright © 2023 Remote Control Technologies Pty Ltd. Images for illustration purposes only. Discover more @ rct-global.com